



gorenje

INFORMATIONSBLAD

MODELL	DFG602-ORA-S
Annual Energy Consumption - AEC_{hood}	167,9 kWh/a
ENERGIKLASS	E
Fluid Dynamic Efficiency - FDE	7,1 %
Fluid Dynamic Efficiency class	F
Light Efficiency - LE_{hood}	3,0 lux/W
Lighting Efficiency Class	G
Grease Filtering Efficiency - GFE_{hood}	76,0 %
Grease Filtering Efficiency class	C
A-weighted Sound Power Emission at minimum speed	240 m ³ /h
Maximum Air Flow in normal use	400 m ³ /h
Air Flow at intensive/boost setting	-
A-weighted Sound Power Emission at minimum speed	52 dB(A) re 1pW
A-weighted Sound Power Emission at maximum speed	63 dB(A) re 1pW
A-weighted Sound Power Emission at intensive or boost speed	-
Power consumption in idle mode - P_0	-
Power consumption in standby mode - P_s	-
Time increase factor	1,7
Energy Efficiency Index - EEI	107,7
Measured air flow rate at best efficiency point - Q_{bep}	240,0 m ³ /h
Measured air pressure at best efficiency point - P_{bep}	213,0 Pa
Maximum air flow - Q_{max}	400 m ³ /h
Measured electric power input at best efficiency point - W_{bep}	199,5 W
Nominal power of the lighting system - W_L	56,0 W
Average illumination of the lighting system on the cooking surface - $E_{average}$	168,0 lux