

**Technical data**

Reaction to fire	EN 13501-1	B -s1 (Hardly flammable)
Formaldehyde emission	EN 717-1	E1 (< 0,05ppm)
Brinell hardness	EN 1534	80N /mm <sup>2</sup>
Thermal resistance	EN 12664	R < 0.10 (m <sup>2</sup> x K)/W
Due to the nature of the material this table shows typical values.		

**Installation**

Installation method	Floating installation, Välinge 2G/5G®
Installation instruction	Download from <a href="http://www.bjelin.com/installation">www.bjelin.com/installation</a>
Under floor heating compatible	Maximal floor surface temperature 27°C
Underlayment material	Foam with CS ≥ 60 kPa & CC ≥ 5 kPa

**Size and package**

	2379 x 223 x 11mm	2379 x 283 x 11mm
Length (mm)	2379	2379
Width (mm)	223	283
Thickness (mm)	11	11
Wear layer thickness (mm)	0,6	0,6
Boards / box	4	4
m <sup>2</sup> / box	2,12	2,69
m <sup>2</sup> / pallet	169,8	169,7
Weight / m <sup>2</sup> (kg)	10	10
Weight / box (kg)	21,2	26,9
Weight / pallet	36,2	41,9

**Maintenance**

Care & Maintenance products	<ul style="list-style-type: none"> <li>- Osmo Opti-set</li> <li>- Osmo Wash &amp; Care</li> <li>- Osmo Licked wax cleaner</li> <li>- Osmo Polyx®-oil</li> </ul>
-----------------------------	---