



gorenje

INFORMATIONSBILAD

MODELL	DR4440X
Annual Energy Consumption - AEC_{hood}	178,8 kWh/a
ENERGIKLASS	E
Fluid Dynamic Efficiency - FDE	11,5 %
Fluid Dynamic Efficiency class	E
Light Efficiency - LE_{hood}	4,5 lux/W
Lighting Efficiency Class	G
Grease Filtering Efficiency - GFE_{hood}	60,5 %
Grease Filtering Efficiency class	E
A-weighted Sound Power Emission at minimum speed	212 m³/h
Maximum Air Flow in normal use	578 m³/h
Air Flow at intensive/boost setting	-
A-weighted Sound Power Emission at minimum speed	45 dB(A) re 1pW
A-weighted Sound Power Emission at maximum speed	67 dB(A) re 1pW
A-weighted Sound Power Emission at intensive or boost speed	-
Power consumption in on mode - P_o	0,95 W
Power consumption in standby mode - P_s	0,62 W
Time increase factor	1,6
Energy Efficiency Index - EEI	102,9
Measured air flow rate at best efficiency point - Q_{bep}	303,0 m³/h
Measured air pressure at best efficiency point - P_{bep}	284,0 Pa
Maximum air flow - Q_{max}	578 m³/h
Measured electric power input at best efficiency point - W_{bep}	208,0 W
Nominal power of the lighting system - W_L	80,0 W
Average illumination of the lighting system on the cooking surface - $E_{average}$	361,0 lux